Journal of Artificial Intelligence Research 14 (2001) 1-28 Submitted 2/00; published 1/01

On Reachability, Relevance, and Resolution in the Planning as Satisfiability Approach

Ronen I. Brafman BRAFMAN@CS.BGU.AC.IL
Department of Computer Science, Ben-Gurion University
P.O.Box 653, Beer-Sheva 84105, Israel

Abstract

In recent years, there is a growing awareness of the importance of reachability and relevance-based pruning techniques for planning, but little work specifically targets these techniques. In this paper, we compare the ability of two classes of algorithms to propagate and discover reachability and relevance constraints in classical planning problems. The first class of algorithms operates on SAT encoded planning problems obtained using the linear and GRAPHPLAN encoding schemes. It applies unit-propagation and more general resolution steps (involving larger clauses) to these plan encodings. The second class operates at the plan level and contains two families of pruning algorithms: Reachable-k and Relevant-k. Reachable-k provides a coherent description of a number of existing forward pruning techniques used in numerous algorithms, while Relevant-k captures different grades of backward pruning. Our results shed light on the ability of different plan-encoding schemes to propagate information forward and backward and on the relative merit of plan-level and SAT-level pruning methods.

1. Introduction

The success of the planning as satisfiability (PAS) approach (Kautz & Selman, 1992, 1996) has led to various attempts to refine the initial methods used and to improve our understanding of its performance. In particular, various methods for generating formulas from planning instances have been compared (Ernst, Millstein, & Weld, 1997), and various systematic alternatives to the original stochastic method have been examined (e.g., Bayardo & Schrag, 1997; Li & Anbulagan, 1997). Still, many issues surrounding this approach are poorly understood. In particular, little is known about the influence of the encoding method on performance.

Concentrating on the two encoding methods proposed by Kautz and Selman (1996), the linear and the GRAPHPLAN-based encodings, we examine their influence on the ability to propagate reachability and relevance information via unit propagation and, more generally, k-clause resolution. We do so by comparing the pruning ability of these techniques to that of a class of algorithms for reachability and relevance analysis that operate on the original problem formulation: Reachable-k and Relevant-k. Reachable-k is a simplified variant of a similar algorithm for state pruning in Markov decision processes (Boutilier, Brafman, & Geib, 1998), while Relevant-k is a natural counterpart used for relevance analysis. Both algorithms provide a coherent framework for discussing different grades of reachability and relevance-based pruning methods that appear in the literature.

Our work is motivated by the growing role that forward and backward pruning methods play in current planning algorithms and the important role of propagation techniques in all SAT solvers used in the planning as satisfiability approach. Unit propagation plays a central role in the Davis-Putnam algorithm (Davis & Putman, 1960) and many of its offsprings (e.g., Crawford & Auton, 1993; Freeman, 1995; Gomes, Selman, & Kautz, 1998; Li & Anbulagan, 1997) and it is used as a preprocessing step when stochastic methods are applied. Moreover, a limited form of binary propagation is used in Crawford's Compact program for simplifying CNF formulas which is utilized in the Blackbox planner (Kautz & Selman, 1999). Our results shed some light on the relationship between these pruning techniques.

The paper is organized as follows. Section 2 provides background material, describing the basic ideas of the PAS framework and the Graphplan algorithm. In Section 3, we discuss Reachable-k, an algorithm for performing reachability analysis, and compare its ability to prune possible actions to that of k-clause resolution. In Section 4 we describe Relevant-k which is similar to Reachable-k and is applied to relevance analysis. Again, we compare it to methods based on resolution. In Section 5 we empirically compare the results of various methods for $k = 1, 2$. We conclude with a discussion of future and related work in Section 6. Proofs appear in the appendix, but their main arguments are described in the body of the paper.

2. Background

The Graphplan algorithm (Blum & Furst, 1997) and the Satplan algorithm (Kautz & Selman, 1996) have profoundly altered the direction of research within the planning community. Two of the main concepts studied in this paper, reachability analysis and plan encodings, have become central to current planning research thanks to these planners. We briefly discuss these planners, and in particular, their aspects pertaining to our topic.

2.1 Reachability Analysis in Graphplan

The purpose of reachability analysis is to discover unreachable states of the world and infeasible actions, i.e., actions that cannot be performed in the course of a successful plan. By discovering such actions ahead of time, we reduce the space that needs to be searched to find a valid plan. In principle, full fledged reachability analysis requires forward search in the space of possible states. This is a very expensive operation, and instead, we can opt for sound, but incomplete methods. Such methods do not discover all the actions that can be ruled out. However, any action that they rule out is infeasible and need not be considered when searching for a plan.

The Graphplan planner provides a good example of the utility of approximate reachability analysis. Graphplan has two main stages: In the first stage, approximate reachability analysis is conducted, yielding a data-structure called the *planning graph* which represents a sound, but incomplete, approximation of the set of states reachable from the initial state. In the second stage, Graphplan searches for a plan over this structure. Graphplan's planning graph construction algorithm presents a particularly good tradeoff between computational complexity and pruning power, and its utility in pruning the search space is attested to by the planner's good performance.

The planning graph construction algorithm can be viewed as generating a list of annotated sets. The odd elements in this list contain sets of propositions. The even elements in this list contain sets of actions. Each such set is annotated with mutual exclusion constraints on its members. Intuitively, the i^{th} action set contains the list of actions that could be performed at the i^{th} step of a concurrent action plan (i.e., a plan allowing for concurrent execution of actions that do not interfere with each other). The i^{th} proposition set contains propositions that could hold after $i-1$ (sets of concurrent) actions have been performed. The mutual exclusion constraints circumscribe these sets by indicating that certain pairs of actions or propositions cannot occur at the same time at a particular stage. Hence, if the propositions p, q appear in the i^{th} proposition set, then it is possible (or more accurately – the algorithm does not rule out the possibility) that an i-step plan applied at the initial state could lead to a world in which p and/or q hold. However, if p and q are marked mutually exclusive then we know that p and q cannot hold *together* after some i-step plan has been performed.

The sets are constructed as follows: The first proposition set contains the propositions that hold at the initial state. The first action set contains the actions that can be performed at the initial state. In general, the i^{th} set of propositions contains the effects of actions in the i-1^{th} action set, and the i^{th} action set contains actions whose preconditions appear in the i-1^{th} set of propositions, provided that their preconditions are not marked as mutually exclusive. Mutual exclusion constraints are added as follows: Two actions are marked mutually exclusive at the i^{th} action set if their preconditions are marked mutually exclusive at the i-1^{th}. Clearly, if all the preconditions of these actions cannot hold at this time point, we cannot perform both actions together at this time point. Another reason for marking actions as mutually exclusive is if they conflict. That is, if one action destroys a precondition or an effect of the other action. Two propositions at the i^{th} proposition set are marked mutually exclusive if all pairs of actions in the i-1^{th} action set that have them as effects are mutually exclusive. When that is the case, there is no way for us to achieve both of these propositions together at this stage.

The initial construction of the planning graph is terminated once all goal propositions appear in the last proposition set. At that point, Graphplan performs a form of regression-based search on the planning-graph structure. If this search fails, the planning graph is extended by one additional layer of actions and one additional layer of propositions and searched again. For more details, see the article by Blum and Furst (1997).

2.2 The Planning as Satisfiability Approach

The Planning as Satisfiability approach (PAS for short), works as follows: given a planning problem and a bound n on the size of the plan, the *plan encoder* generates a propositional formula in conjunctive normal form. This formula has the following property: it is satisfiable iff the planning problem has a solution with at most n time steps. Intuitively, the formula is composed of propositions describing the state of the world throughout the execution of an n-step plan.

The propositional language on top of which the formula is defined contains a proposition for each possible aspect of the world at each time point. For example, suppose we are looking at the blocks' world domain where states are described using the ON and CLEAR relations. In that case, for any pair of blocks x, y, and any time point $0 \leq t \leq n$ we shall introduce a proposition $p_{\mathrm{ON}(x,y,t)}$ which corresponds to x being on top of y at time t. Similarly, for every block x and time point $0 \leq t \leq n$, we shall introduce a proposition $p_{\textsc{clear}(x,t)}$ which corresponds to x being clear at time t.

A truth assignment to the language described above can be viewed as describing the state of the world during the execution of an n-step plan. For instance, if $p_{\textsc{on}(A,B,3)}$ is assigned *true*, then block A is on top of block B at time 3. Of course, most truth assignments to this language would *not* correspond to anything resembling the true state of the world during the execution of an actual plan. For example, both ON(A,B) and ON(B,A) could be assigned *true*. The goal of the encoding scheme is to generate a formula such that any assignment satisfying this formula will correspond to the true state of the world during the execution of an actual plan that achieves the desired goal. Each axiom in this formula places some constraint on the value of these propositions so that the combined effect of these constraints is to ensure that the resulting formula has precisely the desired truth assignments. For example, one type of axiom will be a conjunction of all the propositions corresponding to the initial state. Any truth assignment satisfying this axiom must ensure that these propositions hold at time 0. Another class of axioms could state that if some action a is performed at time t then the world at time $t-1$ must satisfy the preconditions of a. In the next sections we discuss two of the central plan encodings in more detail.

Once an appropriate formula has been generated, it is simplified using various well known techniques. In particular, all simplifiers employ a unit-resolution step (Genesereth & Nilsson, 1987). Unit resolution (also known as *unit propagation*) works as follows: To satisfy a CNF formula, we must satisfy each of its clauses. In particular, if one of the clauses contains a single literal (such a clause is known as a *unit clause*) we immediately know that the variable appearing in this clause must be assigned an appropriate value. Any clause containing the same literal will be satisfied now, and it can be removed from the formula. Any clause c containing the negation of that literal can be resolved against this unit clause, and the resulting clause (which is smaller than c) can replace c. For example, suppose we have the formula $(p) \wedge (\neg q \vee \neg p) \wedge (r \vee p)$. The first disjunct, (p) is a unit clause. Hence, p must be assigned *true*. This makes the third clause, $(r \vee p)$, satisfied. The second clause is now resolved with the first clause, and we replace $(\neg q \vee \neg p)$ by $(\neg q)$. We now have a new unit clause, $(\neg q)$, and so the proposition q must be assigned the value *false*. If we had additional clauses containing q or $\neg q$, we could remove them, or simplify them, as appropriate.

After simplification, we apply our favorite algorithm for finding satisfying assignments, and if one is attained, a *decoder* is used to obtain an actual plan from this solution. If we do not find a satisfying assignment, we increase the value of n (the size of the plan), and try again.

Finally, we note that the BLACKBOX planner (Kautz & Selman, 1999) combines PAS with GRAPHPLAN's reachability analysis. It constructs a planning graph, and uses it to generate a particular plan encoding.

3. Reachability and Resolution

Reachability and relevance analysis form an essential part of successful modern planning algorithms. The most notable example of reachability analysis is GRAPHPLAN's planning graph (Blum & Furst, 1997), and many recent planners employ either reachability analysis (e.g., Bonet, Loerincs, & Geffner, 1997), relevance analysis (e.g., McDermoot, 1996; Nebel, Dimopoulos, & Koehler, 1997), or both (Kambhampati, Parker, & Lambrecht, 1997). The importance of reachability and relevance analysis has been noted in the context of decision-theoretic planning as well. For example, Boutilier and Dearden (1994) employ relevance analysis to reduce the state-space, and Boutilier, Brafman, and Geib (1998) describe a general method for reachability analysis for MDPs. Below, we discuss this method in a simplified form suitable for classical planning problems described using the Strips representation language (Fikes & Nilsson, 1971). In Section 4, we present a counterpart of this method for performing relevance analysis and relate these algorithms to k-clause resolution in the context of SAT-encoded planning problems.

3.1 Propagating Reachability Information

Reachable-k (Boutilier, Brafman, & Geib, 1998) is an algorithm for estimating the states reachable from a given initial state. As formulated, it is quite general and applies to domains with non-deterministic actions and conditional effects. In Figure 1, we present a simplified version of that algorithm, Reachable-k, which deals with deterministic, unconditional actions represented in the Strips representation language. A prolog implementation of Reachable-k is available at www.cs.bgu.ac.il/˜pdm.

An important reason for our interest in Reachable-k is its similarity to the influential planning graph construction of the Graphplan planner (Blum & Furst, 1997). In fact, it generalizes the ideas behind Graphplan's planning graph, which is equivalent to Reachable-2. We use A_i to denote the set of actions feasible i steps from the initial state, S_i to denote the corresponding set of propositions, and CS_i^* to denote constraints on these propositions, such that if $\{p_1, \ldots, p_m\} \in CS_i^*$ then these propositions cannot co-occur after i steps. CA_i^* denotes similar constraints on actions. Here, $* \in \{L, P\}$, where L is used when we restrict our attention to linear action sequences, and P is used when we allow concurrent non-conflicting actions (i.e., actions that do not destroy each others' effects or preconditions and whose preconditions are not constrained not to co-occur). Of course, for $k = 1$ the sets CS_i^* and CA_i^* are empty for all $i \geq 0$. (Actually, as defined, CA_i^L is not empty even when $k = 1$, but it plays no real part in the algorithm, and it should be ignored). Finally, note that in this description, the set of possible actions contains all actions of the form NOOP$[l]$, where l is a literal.

When $k = 2$, S_i and A_i represent the propositional and action levels of Graphplan's planning graph, and CS_i and CA_i^P hold their respective mutual exclusion constraints.

We have not stated a termination condition for Reachable-k, but one can be formulated based on the content of S_i or the index i itself. In the PAS framework, where the number of time-steps is fixed, one would opt for the second alternative. Reachable-k gives us sets of actions and propositions, A_j, S_j, that could occur after the performance of j actions (or j sets of concurrently non-conflicting actions) from the initial state. It is easy to see that Reachable-k is sound in the following sense:

Theorem 1 *If a set of propositions or actions is excluded by Reachable-k at time j then there is no feasible plan in which, at time j, these propositions hold or, respectively, these actions appear.*